



# Installation Instructions

Thank you for your recent purchase of COMPETITOR Racing Lanes. Your order was assembled with marking at 15 meters to identify the point where swimmers doing the backstroke should surface. This point was determined by measuring from the beginning of the first disk on the lane to a point approximately 6 inches shy of 15 meters (48ft. 8 1/2"), which takes into effect the length of the hardware. You will find that the disks used for these markings are manufactured to allow for individual adjustment along the lanes. They are molded with a slight channel to allow for removal and repositioning of the disk without unstringing the lane. This may or may not be necessary depending on the overall length of your pool from eyehook to eyehook.

Once you place all of your lanes in the pool for the first time.

1. Adjust each with similar tension.
2. Be sure that the disks are pushed to one end of the lane. Do this for each lane in the same direction.
3. View the lanes from the side of the pool.
4. Line up with the 15M point to see if all of the lanes match up.
5. If you find a disk out of line, remove it by slightly twisting the disk and pulling it from the cable. This can be done without removing the lanes from the pool.
6. Find the location where you wish to insert it and replace it by slightly twisting the disk back onto the cable.

Again, thank you for your support of COMPETITOR Swim Products.

Manufactured by:  
Competitor Swim Products  
a Division of Richey Industries, Inc.  
910 Lake Road  
Medina, Ohio 44256

Tel: 330-725-4997    Fax: 330-722-3288    E-Mail: [sales@competitorswim.com](mailto:sales@competitorswim.com)